



873 PROLASER® VECTOR



FEATURES

- 1 Horizontal and 2 vertical lines at 90° intersections
- Laser Range:
 - Indoor – 100' (30m)
 - Outdoor – 165' (50m) with detector
- "Tilt" mode for angular layout/marketing
- Strong folding legs for angle mounting in manual mode and height adjustment
- Self-leveling range: $\pm 5^\circ$
- Visual and audible "out of level" warning
- 1/4" tripod thread
- Shock resistant rubber casing
- Accuracy: 0.002"/" (0.2mm/m)


APPLICATIONS

- Framing
- Tiling, cabinets, borders, moldings and trims
- Door and window installation
- Electrical Socket alignment
- Deck installation
- Exterior layout

Option:







- 873 with 886.58 (pole with tripod)

Includes: Belt pouch





873 PROLASER® VECTOR

Dimensions	 unit	 in/cm	 ft³/m³	 lb/kg	 UPC	 EAN
1.76" x 4.96" x 5.08" 12.6 x 12.9 x 16.1cm	12 pieces	30.31" x 10.43" x 10.50" 77 x 26.5 x 16.5cm	1.189ft³ 0.034m³	21.91lb 9.96 kg	739632720689	729100843727
873 Set						
6.10" x 5.31" x 19.29" 15.5 x 13.5 x 49cm	6 pieces	30.31" x 10.43" x 6.50" 19.37 x 18.5 x 10.63cm	2.205ft³ 0.062m³	22.7lb 10.32kg	739632722157	7290100847947