

8991 PROLASER® ELECTROTA™

Self-leveling Rotary Laser Level



















FEATURES

Horizontal or vertical 360° rotating beam

4C

- Plumb up & plumb down dots
- 5 Variable speeds (0, 60, 120, 300 & 600 rpm)
- Laser range up to 300m (980ft) with laser detector
- Self-leveling range ±5°
- Accuracy ±0.1mm/m (0.0001"/")
- · Manual mode for slope construction of up to ±5° on both X & Y planes
- · Scan mode
- Protective rubber over molded casing
- 2 Holes for tripod, horizontal and vertical use, 5/8" thread

INCLUDES

- · Remote cor
- Laser detector
- BeamFinder[™] glasses
- Remote control
- Rechargeable batteries
- 2 Battery brackets for regular and rechargeable batteries
- · Shockproof case

FIELDS OF APPLICATION

- Laying foundations
- · Wall, fence and deck construction

KAPRO

- Laying water and sewage lines
- Drywall, partitions and acoustic ceilings installations



Kapro, the Kapro logo, Plumb Site Dual-View vial, Swivel Plumbsite, Optivision Red, Set & Match, Prolaser, Shark, Postrite and Ergo Grip are trademarks and/or registered trademarks of Kapro Industries Ltd ©2018 Kapro Industries Ltd. PS 30.006 Version D